

Passport of Quality 10PPM type C - 1

| | Min -Max | Fact |
|-------------------------------------|-----------|--------|
| Cetane number | 5,10 - | 51,4 |
| Cetane index | 46,0 - | 53,0 |
| Density at 15 °C | 820 - 845 | 831,0 |
| Polycyclic aromatic hydrocarbons | - 11 | 4,0 |
| Sulphur | - 10 | 6 |
| Flash Point | > 55 - | 58 |
| Carbon residue (on 10pct) | - 0,30 | 0,010 |
| Ash | - 0,01 | 0,0010 |
| Water | - 200 | 46 |
| Particulate Matter | - 24 | 5,2 |
| Copper Strip Corrosion (3h at 50°C) | | 1 |
| Oxidation Stability | - 25 | 5,5 |
| Lubricity, corrected wear scar | - 460 | 362 |
| Diameter (wsd 1,4) at 60°C | | |
| Viscosity at 40°C | 2,00-4,50 | 2,64 |
| Recovered at 250°C | - <65 | 39,3 |
| Recovered at 350°C | 85 | 94,4 |
| 95% Recovered at °C | 360 | 353 |
| Cold Filter Plugging Point | | |
| Winter Grade | - 20 | |
| Summer Grade | 5 | |